

ACKNOWLEDGEMENTS

The two years that I have spent researching Bluetooth technology has been challenging at times, but ultimately very rewarding. Working for the Center for Wireless Telecommunications was an integral part of what I consider an excellent Master's education. First of all, Dr. Dennis Sweeney deserves a great deal of thanks for putting up with my constant badgering of questions and for all his advice and suggestions. I don't know many other advisors who would take that much time out of their day to attend to their graduate students. Secondly, the full extent of this research could not have been achieved without the help of Thomas Rondeau. He possesses a wealth of knowledge on Bluetooth technology, which came in very handy when I ran into problems along the way. Many thanks to him for helping with some of the software coding involved in this thesis, for his suggestions and for assisting me in the measurement process.

So many others have helped me in other ways, for which I am equally grateful. I thank Shelley Johnson for loaning me her microwave oven and the CWT cart to carry around equipment. Also, thanks to everyone else in the CWT who have helped to keep my work personal and sociable.

TABLE OF CONTENTS

ACKNOWLEDGEMENTS	iii
LIST OF TABLES	vii
LIST OF FIGURES	viii
LIST OF EQUATIONS	xi

CHAPTER 1: INTRODUCTORY OVERVIEW

1.1	Scope of the thesis	1
1.2	Relevance of this work	3
1.3	Outline of the thesis	4

CHAPTER 2: BACKGROUND MATERIAL

2.1	Bluetooth Technology Overview	6
2.2	Bluetooth Networking and Operation	6
2.3	Frequency Hopping Spread Spectrum (FHSS)	8
2.4	The Co-Existence Problem	8
2.5	Packet Transmission Overview	9
2.6	Microwave Oven Overview	20
2.7	Previous Methods of Characterizing Ovens	25
2.8	Interference Literature Survey	35

CHAPTER 3: OVEN SPECTRAL CHARACTERIZATION

3.1	Introduction	37
3.2	Spectrum Measurement Concept	37
3.3	Oven Characterization	42
3.4	Conclusion	55

CHAPTER 4: INTERFERENCE EXPERIMENTAL SETUP

4.1	Introduction	57
4.2	Continuous Wave Interference Experiment Setup	57
4.3	Interference Test	61
4.4	Data Processing Procedure	63
4.5	Results of the CW Test	67
4.6	FHSS Selection Program	68

CHAPTER 5: SINGLE CHANNEL PER PREDICTIONS

5.1	Introduction	70
5.2	Bluetooth Receiver Calibration Concept	70
5.3	Receive Power Measurement Procedure	71
5.4	Receive Power Measurements for Channels 50-54	72
5.5	Channel C/I Thresholds and Number of Packet Errors	75
5.6	Theoretical Calculation Results	77

CHAPTER 6: INTERFERENCE EXPERIMENTS SETUP AND RESULTS

6.1	Introduction	80
6.2	Interference Experiment Setup	80
6.3	Experimental Procedure	82
6.4	Environmental Scenarios and Results	82
6.5	Throughput Analysis	120

CONCLUSION	122
-------------------------	------------

APPENDIX A: Serial Cable Pinout and LabView Program.....	124
---	------------

APPENDIX B: Matlab spectral plotting function, ovenpwr.m	127
---	------------

APPENDIX C: Matlab FHSS description and code	128
---	------------

APPENDIX D: Matlab code for the function, received_pwr.m	140
APPENDIX E: Procedure for calculating Experiment Graphs	141
APPENDIX F: Matlab code for the function, channel_counter.m	144
APPENDIX G: Results of other Experimental Scenarios	145
REFERENCES	148
VITA	150

LIST OF TABLES

Table 2.5.2-1. ACL link packet types	11
Table 2.5.2-2. ACL packet types	15
Table 2.6.3-1. Vertical and horizontal polarization correlation results for measured ovens	27
Table 3.3.1. Oven Specifications	44
Table 5.4.1. Received powers for channels 50-54 with the slave unit connected	74
Table 5.6.1. Single-channel calculations	78
Table 6.4.1. Accuracy of Calculated versus Measured Packet Errors	92
Table 6.5.1. Throughput results of the Emerson oven experiments	121
Table 6.5.2. Throughput results of the G.E. oven experiments	121

LIST OF FIGURES

Figure 2.2.1. The Bluetooth Stack	7
Figure 2.3.1. Bluetooth available bandwidth	8
Figure 2.5.1. Standard packet format	10
Figure 2.5.2-2. Standard packet format	15
Figure 2.5.3. Rate 1/3 FEC bit-repetition encoding scheme	16
Figure 2.5.4-1. HEC generation and checking	18
Figure 2.5.4-2. CRC generation and checking	18
Figure 2.6.1-a1. Zero-span spectrum of a residential microwave oven	22
Figure 2.6.1-a2. Max-hold spectrum for a residential microwave oven	22
Figure 2.6.1-b. Max-hold plot for a two magnetron commercial microwave oven	23
Figure 2.6.3-1. Antenna polarization variation with Oven #4	26
Figure 2.6.3-2. Antenna polarization variation with Oven #8	26
Figure 2.6.3-3. Measurement antenna oriented in the H-plane	28
Figure 2.6.3-4. Measurement antenna rotated 90°	28
Figure 2.7.3-1. NTIA measurement of oven Time vs. Amplitude at 2450 MHz	33
Figure 2.7.4. Relating Time-and Frequency-Domain measurements to actual signal time-frequency characteristics	34
Figure 3-2.1. LabView Data Acquisition Program User Interface	39
Figure 3.2.2. Experimental setup for collecting oven emissions and Bluetooth data	41
Figure 3.3.2-1. Sharp-Carousel Oven PSD measured over a 63 second interval	46
Figure 3.3.2-2. Overhead shot showing the Sharp-Carousel Oven PSD	47
Figure 3.3.2-3. General Electric Oven PSD measured over a 60 second interval	48
Figure 3.3.2-4. Overhead shot showing the General Electric Oven PSD	49
Figure 3.3.2-5. Emerson (MW8126 W/S/D) Oven PSD measured over a 62 second interval	50
Figure 3.3.2-6. Overhead shot showing the Emerson (MW8126 W/S/D) Oven PSD	51
Figure 3.3.2-7. Emerson (MW8107WA) Oven PSD over a 65 second interval	52
Figure 3.3.2-8. Overhead shot showing the Emerson (MW8107WA) Oven PSD	53

Figure 4.2.1. CW Interfering Spectral Point at 2.440 GHz	59
Figure 4.2.2. CW Experimental Setup	60
Figure 4.3.1. Tektronix Protocol Analyzer's Baseband log file	62
Figure 4.4.1. Bluetooth Handshaking Transmission without interference	64
Figure 4.4.2. CW Interference on Bluetooth Handshaking Test	65
Figure 4.4.3. CW Interference on Bluetooth Data Transmission	66
Figure 5.4.1. Bluetooth Receive Power measurement setup	73
Figure 5.4.2. Slave unit's transmitted and received signals	75
Figure 6.2. Experimental setup for collecting oven emissions and Bluetooth data	81
Figure 6.4.1. Oven in the same room with the piconet	84
Figure 6.4.2. DM Packets transmitted over one meter without oven interference	85
Figure 6.4.3. DH Packets transmitted over one meter without oven interference	86
Figure 6.4.4. Emerson interfering from the Bluetooth Lab	89
Figure 6.4.5. Emerson affecting DM1 transmission	90
Figure 6.4.6. Emerson affecting DH1 transmission	91
Figure 6.4.7. General Electric interfering from the Bluetooth Lab	93
Figure 6.4.8. G.E. oven affecting DM1 transmission	94
Figure 6.4.9. G.E. oven affecting DH1 transmission	95
Figure 6.4.10. Oven in the room across the hall with the door open	96
Figure 6.4.11. Emerson affecting DM1 transmission from other room	98
Figure 6.4.12. Emerson affecting DH1 transmission from other room	99
Figure 6.4.13. GE affecting DM1 packets from across the hall	100
Figure 6.4.14. GE affecting DH1 packets from the other room	101
Figure 6.4.15. Oven and slave in room across the hall with the door open	102
Figure 6.4.16. Emerson and slave in room across hall affecting DM transmission	103
Figure 6.4.17. Emerson affecting DH transmission when oven and slave are in room across the hall	104
Figure 6.4.18. Environmental layout of the CWT's Graduate Student Lab	106
Figure 6.4.19. Oven in the Grad lab affecting DM transmission	108
Figure 6.4.20. Oven in Grad Lab affecting DH transmission	109
Figure 6.4.21. Oven behind drywall affecting DM transmission	111

Figure 6.4.22. Oven behind drywall affecting DH transmission	112
Figure 6.4.23. Emerson in stairwell affecting DM transmission	114
Figure 6.4.24. Emerson in stairwell affecting DH transmission	114
Figure 6.4.25. Experimental setup in the outdoor environment	115
Figure 6.4.26. Interference results for a 30 m link distance shows poor performance .	116
Figure 6.4.27. Emerson's effects on DM1 transmission for a 72 m link distance	118
Figure 6.4.28. Emerson's effects on DH1 transmission for a 72 m link distance	119

LIST OF EQUATIONS

Equation 2.7.1-1	31
Equation 2.7.1-2	31
Equation 4.2.1	60
Equation 4.2.2	60
Equation 5.2.1	70
Equation 5.5.1	76
Equation 5.5.2	76
Equation 5.5.3	77