

Table of Contents

Abstract	ii
Acknowledgements	iii
Table of Contents	iv
List of Figures	vii
List of Tables	ix

Chapter 1

Introduction	1
1.1 Background	1
1.2 Research Objectives	3
1.3 Research Contributions	3
1.4 Literature Review and Technology Introduction	4
1.4.1 Vibration Based Non-Destructive Evaluation Techniques	4
1.4.2 Impedance-based Health Monitoring Technique	7
1.4.3 Self-Repairing Structures	11
1.4.4 Shape Memory Alloy Technology	14
1.5 Outline of Thesis	18

Chapter 2

Low Cost Impedance Measurements	20
2.1 Introduction	20
2.2 Conventional Impedance Measurements	20
2.3 Alternative Impedance Measuring Circuits	23
2.4 Proof-of-Concept Experiments	26
2.4.1 Bolted Joint Experiment	26
2.4.2 Pipeline Experiment	29
2.4.3 Detecting Damage in a Composite Beam	32
2.5 Conclusions	34

Chapter 3

Bolted Joint Diagnostics	36
3.1 Introduction	36
3.2 Literature Review	36
3.3 Investigation of Natural Frequency Variations with Changes in Torque ...	37
3.3.1 Modal Experiment	38
3.3.2 Impedance Experiment	38
3.3.3 Results	41
3.4 Characterization of Damping	42
3.4.1 Experimental Configuration	43
3.4.2 Analysis of Experimental Data	46
3.4.3 Mathematical Model	48
3.4.4 Experimental Results	51
3.4.5 Analytical Results	54
3.5 Conclusions	57

Chapter 4

Adaptive Bolted Joints	59
4.1 Introduction	59
4.2 Heating Model	60
4.3 Resistive Heating Experiment	65
4.4 External Heater Experiment	72
4.5 Ring Sizing	77
4.6 Conclusions	79

Chapter 4

Conclusion and Future Work	81
5.1 Conclusion	81
5.2 Future work	84

References	85
-------------------------	-----------

Appendix A

Mathematica Code for SMA Ring Heating Model 91

Vita 94

List of Figures

Figure 1.1	1-D model representing a PZT-driven dynamic structural system	9
Figure 1.2	Atomic arrangements of alloys exhibiting the shape memory effect	15
Figure 1.3	Temperature hysteresis (from Raychem, Actuator Design)	16
Figure 1.4	Schematic showing superelasticity of SMA	17
Figure 1.5	The Frangibolt separation system	18
Figure 2.1	Self-sensing actuator circuit (rate of strain sensor).....	22
Figure 2.2	Circuit for approximating PZT impedance	23
Figure 2.3	Impedance approximating circuit with amplification	24
Figure 2.4	FFT Analyzer and current measuring circuit	25
Figure 2.5	Bolted beam schematic	27
Figure 2.6	Impedance method measurement comparison	27
Figure 2.7	Low cost response to simulated damage	28
Figure 2.8	Traditional response to simulated damage	29
Figure 2.9	Portion of pipeline structure	30
Figure 2.10	Close up of joint showing location of PZT's	30
Figure 2.11	Comparison of low cost to traditional method on pipeline structure	31
Figure 2.12	Damage metric for traditional and low cost impedance	32
Figure 2.13	Undamaged composite beam with PZT attached	33
Figure 2.14	Low-cost impedance box, SigLab Analyzer and PC	33
Figure 2.15	Damage at far end of beam	33
Figure 2.16	Damage at end near PZT	33
Figure 2.17	Impedance measurements with accumulating damage	34
Figure 3.1	Magnitude of FRF for varying torques	38
Figure 3.2	Example of impedance measurements and resulting transfer impedance	39
Figure 3.3	Impedance based and modal based response of joint at 40 ft-lbs	41
Figure 3.4	Natural frequency variation of modal data with torque level	42
Figure 3.5	Natural frequency variation of transfer impedance data with torque level ..	42
Figure 3.6	Schematics of beam specimens	43
Figure 3.7	Jointed beam schematic	43

Figure 3.8 Segmented beam geometry	44
Figure 3.9 Solid beam geometry	44
Figure 3.10 Beam instrumentation	45
Figure 3.11 Sample frequency response functions of jointed and solid beams	46
Figure 3.12 Nonlinear finite element model schematic	50
Figure 3.13 Typical response time history and its envelope for the jointed beam	51
Figure 3.14 Typical response time history and its envelope for the monolithic beam ..	52
Figure 3.15. Estimates of local linear damping factor for the monolithic beam	52
Figure 3.16 Estimates of local linear damping factor for the jointed beam	53
Figure 3.17 Computed velocity response of linear system, and its envelope	55
Figure 3.18 Computed velocity response of nonlinear system, and its envelope	55
Figure 3.19 Estimates of local linear damping factor for the linear beam model	56
Figure 3.20 Estimates of local linear damping factor for the nonlinear beam model	56
Figure 4.1 Schematic of SMA ring	62
Figure 4.2 Heating model of ring with no insulation	62
Figure 4.3 Heating model of ring with ceramic washers	64
Figure 4.4 Schematic of beam used in heating experiments	66
Figure 4.5 Self-healing by resistive heating configuration	66
Figure 4.6 Resistive heating experiment impedance from 2.8 kHz to 3.2 kHz	67
Figure 4.7 Resistive heating experiment impedance from 5 kHz to 7 kHz	68
Figure 4.8 Resistive heating experiment impedance from 10 kHz to 12 kHz	68
Figure 4.9. Resistive heating experiment impedance from 12.5 kHz to 15 kHz	70
Figure 4.10 Resistive heating experiment impedance from 15 kHz to 18 kHz	70
Figure 4.11 Resistive heating experiment impedance from 30 kHz to 35 kHz	71
Figure 4.12 Bolted joint with heater	73
Figure 4.13 External heater experiment impedance from 2.8 kHz to 3.2 kHz	74
Figure 4.14 External heater experiment impedance from 7 kHz to 12 kHz	75
Figure 4.15 External heater experiment impedance from 15 kHz to 18 kHz	76
Figure 4.16 Ring showing uneven actuation	76

List of Tables

Table 3.1	Natural frequencies and damping ratio from analysis of modal data	40
Table 3.2	Natural frequencies and damping ratio from analysis of impedance data	40
Table 4.1	SMA ring properties	61
Table 4.2	Ceramic ring properties	63