

## Table of Contents

<b>Title Page</b>	<b>i</b>
<b>Abstract</b>	<b>ii</b>
<b>Acknowledgements</b>	<b>iii</b>
<b>Table of Contents</b>	<b>iv</b>
<b>List of Illustrations</b>	<b>vii</b>
<b>List of Tables</b>	<b>xi</b>
<b>Chapter 1 – Introduction</b>	<b>1</b>
1.1 Importance of Magnetic Field Measurement	1
1.2 Magnetic Field Sensors	2
1.3 Optical Fiber Sensor based Measurements	5
1.4 Technical Objectives	8
<b>Chapter 2 – Extrinsic Fabry-Perot Interferometer Measuring Magnetic Field</b>	<b>11</b>
2.1 Principle of the Basic EFPI Sensor	11
2.2 Basic Sensor Design	13
2.3 Magnetic Properties of Ferromagnetic Materials	14
2.4 Investigation of Magnetostrictive Characteristics	16
2.5 Sensor Material Selections	22
<b>Chapter 3 – Sensor Performance Enhancement</b>	<b>24</b>
3.1 New Sensor Design	24

3.2	Sensor Gage Performance Improvement	25
3.2.1	Transverse Field Annealing	25
3.2.2	Enhancement of the Performance of Transverse Field Annealed Metglas Wire	29
3.2.3	Enhancing Sensor Gage Sensitivity	32
3.3	Sensor Temperature Compensation	34
3.3.1	Temperature Compensation Scheme	34
3.3.2	Precise Evaluation of CTEs in Specific Sensor Geometry	40
3.3.3	Mathematical Adjustment for Temperature Compensation	42
3.3.4	Result of Temperature Compensation	44
3.4	Improvement of Fringe Visibility	46
3.5	Sensor Biasing and Packaging Methods	48
3.5.1	Sensor Biasing	48
3.5.2	Sensor Packaging	50
3.6	Signal Demodulation	52
3.6.1	Introduction to Signal Demodulation	52
3.6.2	Principle of Quadrature Signal Demodulation	53
3.6.3	Circuit Design for Quadrature Signal Demodulation	55
3.6.4	Evaluation of Quadrature Signal Demodulation Circuit	58
3.6.5	Signal Demodulation Circuitry with Intensity Normalization	64
3.7	System Performance Analysis	66

## **Chapter 4 – Design of Vector Magnetic Field Sensor System 69**

4.1	3-Dimensional Vector Field Representation	69
4.2	Design of Vector Field Measuring System	72
4.2.1	Sensor Head Design	72
4.2.2	System Design with 3 Separate Laser Sources	73
4.2.3	System Design with Single Laser Source	74
4.2.4	Channel Amplifier Design	75

4.3	Microprocessor-based Signal Demodulation and Processing	76
4.4	Fabricated Vector Field Measuring System	79
4.5	System Calibration	81
4.5.1	Experimental Setup	81
4.5.2	Calibration Procedures	83
4.5.3	Experimental Results	83
<b>Chapter 5 – Active/Passive Hybrid Temperature Compensation and Signal Demodulation</b>		<b>97</b>
5.1	Concept of Active/Passive Hybrid Temperature Compensation and Demodulation	97
<b>Chapter 6 - Conclusions</b>		<b>100</b>
<b>References</b>		<b>102</b>
<b>Vita</b>		<b>104</b>

## List of Illustrations

Figure 2.1	Typical EFPI sensor structure.	12
Figure 2.2	Basic sensor design used to evaluate magnetostrictive characteristics of candidate materials.	14
Figure 2.3	Magnetostriction of $Tb_{1-x}Dy_xFe_2$ as a function of $x$ .	15
Figure 2.4	Schematic of the experimental setup used for the evaluation of candidate magnetostrictive materials.	17
Figure 2.5	Magnetostriction as a function of magnetic field intensity for Terfenol-D.	18
Figure 2.6	High field magnetostrictive characteristics of Metglas ( $Fe_{78}B_{13}Si_9$ ) ribbon.	19
Figure 2.7	Low field magnetostrictive characteristics of Metglas ( $Fe_{78}B_{13}Si_9$ ) ribbon.	20
Figure 2.8	Noise reduction by a digital signal processing.	21
Figure 2.9	DC-magnetic field response of Metglas wire ( $Fe_{77.5}B_{15}Si_{7.5}$ ).	22
Figure 3.1	A modified EFPI based sensor design.	24
Figure 3.2	Domain structure of transverse annealed material.	26
Figure 3.3	Domain structure of the material after applying longitudinal field $\vec{H}$ .	26
Figure 3.4	Preliminary field annealing system.	27
Figure 3.5	Annealing temperature curve.	28
Figure 3.6	DC-magnetic field response of Metglas wire ( $Fe_{77.5}B_{15}Si_{7.5}$ ).	29
Figure 3.7	Enhancement of magnetostriction, high magnetic field, with increasing annealing field.	30
Figure 3.8	Enhancement of magnetostriction, low magnetic field, with increasing annealing field.	30
Figure 3.9	High field transverse annealing system for enhancing sensor performance.	32

Figure 3.10	Magetostriktion of the new materials.	34
Figure 3.11	Simple sensor design with a borosilicate compensator.	35
Figure 3.12	Time domain sensor output signal due to large measurand for an EFPI-based sensor.	36
Figure 3.13	A model for extracting parameters.	38
Figure 3.14	Simple sensor design for evaluation of passive temperature compensation in an EFPI based weak magnetic field sensor.	39
Figure 3.15	Effective passive temperature compensation in EFPI based weak magnetic field sensor.	39
Figure 3.16	A temperature compensated sensor for evaluating CTEs of material used.	40
Figure 3.17	Sensor geometry to obtain exact temperature compensation by calculating $\Delta L$ .	42
Figure 3.18	Uncalibrated sensor output (83.0% compensation).	44
Figure 3.19	Calibrated sensor output (94.96% compensation).	45
Figure 3.20	Temperature compensated sensor output (98%).	46
Figure 3.21	Modified sensor gage endface.	47
Figure 3.22	Improvement in the fringe visibility.	48
Figure 3.23	DC bias method using single permanent magnet.	49
Figure 3.24	Using two, small permanent magnets for DC biasing the sensor.	50
Figure 3.25	Packaging scheme using V-grooved base.	51
Figure 3.26	Packaging scheme using glass tubes.	52
Figure 3.27	90° phase shifted sensor system for quadrature signal demodulation.	53
Figure 3.28	A detailed presentation of 90° phase shifted sensor system.	55
Figure 3.29	Block diagram of the analog quadrature demodulation circuit.	57
Figure 3.30	Circuit diagram for the analog demodulator.	57

Figure 3.31 Output voltage vs change in phase.	59
Figure 3.32 Output voltage vs change in phase.	61
Figure 3.33 Output voltage vs change in phase.	62
Figure 3.34 Output voltage vs change in phase.	64
Figure 3.35 Block diagram of signal demodulation circuitry with intensity normalization.	65
Figure 3.36 Demodulation circuit diagram with intensity normalization.	66
Figure 3.37 Output of sensor (Tube3).	67
Figure 3.38 Output of sensor (Tube4).	68
Figure 3.39 System calibration curve (without ceramic insulator).	68
Figure 4.1 Vector representation of magnetic field.	69
Figure 4.2 Sensor arrangement.	71
Figure 4.3 Initial operating point of the sensors.	71
Figure 4.4 Sensor head for vector magnetic field measurement.	72
Figure 4.5 Design using three separate laser diodes.	73
Figure 4.6 Design using single laser diode.	74
Figure 4.7 Preamplifier circuitry for a single channel.	76
Figure 4.8 Components of the electronic signal processing system.	76
Figure 4.9 Block diagram of QPS signal demodulation scheme.	77
Figure 4.10 Block diagram of microprocessor-based signal demodulation system.	78
Figure 4.11 Experimental arrangement of magnetometer system.	79
Figure 4.12 Electronic signal processing system box.	80
Figure 4.13 Calibration setup.	80
Figure 4.14 Complete experimental setup.	84

Figure 4.15 Schematic of a single axis sensor assembly.	81
Figure 4.16 Experimental setup.	82
Figure 4.17 (a) Low field response of sensor 3 (X-axis).	84
Figure 4.17 (b) High field response of sensor 3 (X-axis).	85
Figure 4.18 Field response of sensor 2 (X-axis).	85
Figure 4.19 (a) Low field response of sensor 4 (Y-axis).	86
Figure 4.19 (b) High field response of sensor 4 (Y-axis).	87
Figure 4.20 Field response of sensor 5 (Y-axis).	87
Figure 4.21 (a) Low field response of sensor 6 (Z-axis).	88
Figure 4.21 (b) High field response of sensor 6 (Z-axis).	89
Figure 4.22 Low field response of sensor 7 (Z-axis).	89
Figure 4.23 Calibration curve for X-axis.	90
Figure 4.24 Calibration curve for Y-axis.	91
Figure 4.25 Calibration curve for Z-axis.	91
Figure 4.26 X-axis system response.	92
Figure 4.27 Y-axis system response.	93
Figure 4.28 Z-axis system response.	93
Figure 4.29 First stage of system calibration for X-axis.	95
Figure 4.30 Second stage of system calibration for X-axis (Final system out representation).	96
Figure 5.1 Operating regions of the sensor.	97

## List of Tables

Table 3.1	Properties of new Metglas material	33
Table 3.2	CTE values from various combinations	43
Table 3.3	Evaluation of sensors for exact temperature compensation	45
Table 3.4	Initial phase = 0 deg	58
Table 3.5	Initial phase = 90 deg	60
Table 3.6	Initial phase = 180 deg	61
Table 3.7	Initial phase = 0 deg	63
Table 4.1	Resource comparison for three diode and single-diode designs	75